

Class	Function/Method	Parameters	Return
	desanitize(\$entry)		mixed or FALSE
	file_cull_contents(\$filename, \$offset = 0, \$bytes = null, \$whence = SEEK_SET, \$data = null)		mixed or FALSE
	file_place_contents(\$filename, \$data)		int or FALSE
Mimesis		(\$cwd, \$table, \$struct)	
Mimesis::	table(\$path = null)		str
Mimesis::	struct(\$path = null)		str
Mimesis::	tableExists()		bool
Mimesis::	structExists()		bool
Mimesis::	refresh(\$sort = false, \$atomic = true)		bool
Mimesis::	entries()		Array
Mimesis::	getRow(...)		Array or FALSE
Mimesis::	query()		Array or FALSE
Mimesis::	insertRow(\$data, \$atomic = true)		bool
Mimesis::	deleteRow(\$row, \$atomic = true)		bool
Mimesis::	deleteTable(\$atomic = true)		bool
Mimesis::	renameRow(\$old, \$new, \$atomic = true)		bool
Mimesis::	lock(\$polling = null, \$override = true)		bool
Mimesis::	release()		bool
Mutex		(\$filename)	
Mutex::	acquireLock(\$polling = null, \$override = true)		bool
Mutex::	releaseLock()		bool
Mutex::	lockTime()		int or FALSE
Mutex::	lockID()		str or FALSE
Mutex::	lockAbort()		
Mutex::	lockOverride()		bool
Polarizer		(\$keys, \$values = null)	
Polarizer::	getKeys()		str or FALSE
Polarizer::	getValues()		str or FALSE
Polarizer::	getArr()		Array or FALSE
	sanitize(\$entry)		string
	singularID(\$prefix = 'sid', \$tempdir = null)		str or FALSE
	str_offsets(\$haystack, \$needle, \$offset = 0)		Array or FALSE
	str_r_pos(\$haystack, \$needle, \$offset = 0)		int or FALSE